

DH-590M

Conference Control Unit



DESCRIPTION

The DH-590M Conference Control Unit is an advanced central management system designed to facilitate seamless and structured discussions in professional meeting environments. Supporting both DH-592C Chairman Units and DH-592D Delegate Units, it ensures real-time microphone control, multiple discussion modes, and intuitive system operation. With its 4.3-inch IPS touchscreen display, users can easily configure settings, monitor active microphones, and manage participant engagement for a smooth and efficient conferencing experience.

Its GSM interference protection eliminates disruptions from mobile signals, guaranteeing clear and uninterrupted audio transmission. Built with hot-swappable connectivity, the DH-590M allows microphone units to be connected or replaced without interrupting ongoing discussions. The unit features multiple conference modes, including first-in-first-out (FIFO), last-in-first-out (LIFO), chairman priority mode, and full open mode, providing flexibility for different meeting formats.

A speaker limit function enables precise control over the number of active microphones, ensuring an organized and balanced discussion environment. With balanced audio output and RS232 connectivity, it seamlessly integrates with external sound reinforcement and recording systems for enhanced audio management.

FEATURES

Conference Management & Control

- Supports multiple meeting modes including FIFO, LIFO, restricted mode, chairman mode, and full open mode for flexible discussion management.
- Speaker limit function allows customization of the maximum number of active microphones, ensuring structured and balanced discussions.

Seamless Microphone Integration

- Compatible with DH-592C Chairman Units and DH-592D Delegate Units, allowing seamless communication and system expansion.
- Supports up to 120 microphone units with hot-swappable connectivity for easy maintenance and installation.

Advanced Audio Processing

- Integrated audio mixing and automatic gain control (AGC) ensures clear speech transmission without distortion.
- Built-in GSM immunity prevents interference from mobile signals, delivering uninterrupted audio clarity.

Touchscreen Interface & System Control

- Equipped with a 4.3-inch full-color IPS capacitive touchscreen for intuitive system configuration and monitoring.
- Provides real-time status updates for active microphones, speaker settings, and meeting modes.

External Audio & Recording Connectivity

- Balanced audio output and RS232 control interface enable seamless integration with external sound reinforcement and recording devices.
- Allows connection to broadcasting, sound amplification, and recording systems for enhanced meeting documentation.

TECHNICAL SPECIFICATIONS

Model	DH-590M Conference Control Unit
Compatible Units	Supports DH-592C Chairman Unit & DH-592D Delegate Unit
Material & Finish	Aluminium Casing, Matte Black Finish
Conference Modes	FIFO, LIFO, Restricted Mode, Chairman Mode, Full Open Mode
Microphone Connectivity	4 x RJ45 Microphone Unit Interfaces, 4 x 8-Core Interfaces
Maximum Capacity	Supports up to 120 Microphone Units
System Control	4.3-inch Full-Color IPS Capacitive Touchscreen for System Configuration & Monitoring
Speaker Limit Function	Configurable for 1 to 12 Active Microphones at a Time
Microphone Activation	Push-to-Talk for Delegates, Chairman Override Control
XLR Microphone Input (Nominal)	-56dBV
XLR Microphone Input (Maximum)	-26dBV
Frequency Response	30Hz – 20kHz
Total Harmonic Distortion (THD)	<0.1%
Sample Rate	44.1kHz
Hot-Swappable Microphone Support	Yes (Plug-and-Play Replacement Without System Interruption)
Digital Audio Feedback Suppression (DAFS)	Yes
Auto Shutdown	Timed Shutdown & Automatic Deactivation for Energy Efficiency
Encryption	Yes, IEEE 802.1x Security Protocol
GSM Immunity	Yes, Shielded Against Mobile Signal Interference
Power Supply	AC 100V-240V, 50/60Hz
Output Interfaces	Balanced Audio Output, RS232 Control Port
Recording & External Audio Support	Compatible with External Sound Reinforcement & Recording Devices
Operating Temperature	-10°C to 50°C
Weight	Approx. 4.5kg
Dimensions	19-Inch Standard Rack Mountable Unit
Application	Boardrooms, Auditoriums, Government & Corporate Conference Systems

HQ Asia
 asia@anistonav.com
anistonav.com

Europe
 europe@anistonav.com
anistonav.com/europe

United States
 unitedstates@anistonav.com
anistonav.com/us/

Middle East
 uae@anistonav.com
anistonav.com/uae



ANISTON TECHNOLOGIES LLP
 anistonav.com
 E-mail: info@anistonav.com

All information copyright Aniston Technologies LLP, 2024. Aniston Technologies LLP reserves the right to change this document without notice.

