

DH-592C

Wired Chairman Unit



DESCRIPTION

The DH-592C Wired Chairman Unit is a high-performance conference microphone system designed to provide structured communication and efficient meeting control. Featuring a durable aluminum alloy microphone, it ensures reliable voice pickup with enhanced durability, making it suitable for long-term professional use.

The unit is equipped with a built-in speech timer, which automatically starts counting when the microphone is activated, allowing for better management of speaking time during discussions. This feature ensures that meetings remain well-structured and time-efficient in conference halls, boardrooms, and corporate environments.

For seamless usability, the DH-592C includes a red glowing LED ring on the button, providing real-time microphone status visibility, allowing participants to easily determine when the microphone is active. Additionally, it is equipped with three function buttons that enable users to modify time, date, and language settings, making it adaptable to different conference setups. The chairman priority override function allows the chairman to take control of discussions when necessary, ensuring smooth, uninterrupted communication and maintaining order in professional meetings.

FEATURES

Durable Aluminum Alloy Microphone

- High-quality aluminum alloy construction ensures long-lasting durability and reliable voice transmission.
- Provides consistent audio clarity while maintaining a lightweight and sturdy design for professional environments.

Integrated LED Status Indicator

- Features a red glowing LED ring on the button that provides real-time microphone activation status.
- Offers clear visual feedback, allowing participants to easily determine when the microphone is active.

Built-in Speech Timer

- Automatically starts counting when the microphone is activated, helping manage speaking time during discussions.
- Ensures efficient time management, making meetings more structured and organized.

Chairman Priority Override Function

- Allows the chairman to mute or take control over all delegate microphones, ensuring structured discussions.
- Ensures seamless moderation for efficient and controlled meeting management.

Seamless System Integration

- Fully compatible with the DH-590M Conference Control Unit for centralized microphone and discussion management.
- Supports hot-swappable connectivity, allowing microphones to be replaced or added without disrupting the system.

TECHNICAL SPECIFICATIONS

Model	DH-592C Wired Chairman Unit
Microphone Material	Aluminum Alloy Microphone
Microphone Stem	Detachable, High-Strength Anodized Aluminum Alloy
Indicator	Red Glowing LED Ring on Button for Real-Time Status Display
Speech Timer	Built-in Timer Starts Counting When Microphone is Activated
Multilingual Support	Supports Simplified English, and Traditional English
Function Buttons	Three Buttons for Modifying Time, Date, and Language Settings
Shutdown Function	Voice-Controlled Auto Shutdown
Priority Control	Chairman Priority Override Button
Power Supply	DC 24V (Powered by System Host)
Power Consumption	2W
Connection Type	8-Core and RJ45 Interface for Flexible Connectivity
GSM Immunity	Yes, Shielded Against Mobile Signal Interference
Base Design	Anti-Slip Base with Noise Isolation
Microphone Design	Standard Plug-In with High-Strength Anodized Aluminum Alloy
Microphone Nominal Input	85 dB SPL
Frequency Response	125Hz - 15,000Hz
Audio Quality	16-bit Signal
Windshield	Replaceable
Operating Temperature	-10°C to 50°C
Weight	Approx. 1.2kg
Dimensions	200mm × 150mm × 60mm
Application	Conference Rooms, Boardrooms, Auditoriums

Aniston Technologies LLP

HQ Asia
 asia@anistonav.com
anistonav.com

Europe
 europe@anistonav.com
anistonav.com/europe

United States
 unitedstates@anistonav.com
anistonav.com/us/

Middle East
 uae@anistonav.com
anistonav.com/uae



ANISTON TECHNOLOGIES LLP
 anistonav.com
 E-mail: info@anistonav.com

All information copyright Aniston Technologies LLP, 2024. Aniston Technologies LLP reserves the right to change this document without notice.

